

Corabit curbstone Mastic Putty PRODUCTDATASHEET

- Cold-processable
- High stability
- Bridging tensions



Corabit Curbstone Mastic Putty is a bitumen-based plastic joint putty for filling curbstone and other joints, e.g. between steps and prefabricated concrete elements in stadiums, sports arenas and the like.

Prime the thoroughly cleaned and dry joint with **Corabit FB Primer**. After the primer has dried, press in the **Corabit Curbstone Putty** with a trowel and jointing iron and then smooth. It is recommended to tape the Curbstone before backfilling to avoid unwanted contamination on it. Dipping the jointing tool in lukewarm water from time to time during jointing also makes it easier to work. The maximum joint width is 15 mm.

Consumption

The consumption is approx. 1.5 kg/l joint space.

Specifications

Property	Unit	Typical value
Density	g/cm ³	≈ 1,5
Softening point ring and cone	°C	≥ 100
Stability Model Joint	°C	≥ 60

DELIVERY FORM

Corabit FB-Primer in containers of 1 l / 5 l / 10 l and in the 600 ml spray can

	Container weight [kg]	Container type [-]	Container / Pallet [Stk.]
Corabit Curbstone Mastic Putty	12	Hobbock	45

STORAGE

The containers must be stored in a cool and dry place. Direct sunlight should be avoided.

The information in this publication is based on our knowledge and experience. The given instructions and instructions for use have been compiled to the best of our knowledge based on our experiments and experience. The best results are achieved with the proper and professional use of our products. Any intellectual property rights as well as existing laws and regulations must be observed by the recipient of our products on his or her own responsibility. In all other respects, our general terms and conditions apply.
-- Rev.: 01_10.10.2024 --